

## RS-II

### Remote Tank Monitoring software

This Software can monitor tank status remotely by internet. It provides a real-time monitoring of fuel level, water level and product temperature on computer at head office. It is required Static Public IP for Server.



#### Features

- Easy installation and operation
- Enough room for expanded functions
- Support Report of Delivery and inventory
- Support alarm report
- Support shift report
- Support search by time or/and by tank
- User-defined alarms
- Report can be saved as PDF or Excel
- Support GSM



Tank No	Alarm Type	Alarm V...	Happening Time
02	VHAlarm	98.6	2009-4-19 10:12:58
D1	VHAlarm	56	2009-4-19 10:13:05
D3	Connection interrupted		2009-4-19 10:13:09
D4	Connection interrupted		2009-4-19 10:13:10
D1	VHAlarm	56	2009-4-19 10:14:00
D2	VHAlarm	98.5	2009-4-19 10:14:00
D4	Connection interrupted		2009-4-19 10:47:23
D4	HHAlarm	2667.5	2009-4-19 10:47:59
D3	HHAlarm	2479.5	2009-4-19 10:49:19
D4	HHAlarm	2774	2009-4-19 10:49:29

#### Reference devices associated

##### Reference specification of SERVER

Brans Lenovo IBM,  
Model X3650M5 8871i05 E5-2603v4  
Mainframe 2603V4, 6-cores, 1.7G CPU,  
single, power, internal storage 32G+2 pcs  
hard disk 300G 10K SAS

##### Reference specification of UPS

Brand SANTAK  
Model C1K  
Rated power 800W, rated capacity  
1000VA, output 10A, GB\*2, LED display,  
duration 4.5 hours.

WINDBELL Measurement and Control  
No.9 Changchun Road, High-Tech  
development Zone, Zhengzhou, China  
Tel/Fax: +86 371 6030 1609; 6030 1612

emily@windbelltek.com  
www.windbellgauge.com

October 2016